



Vertical Pivot Gate & Operator Specifications

MODEL:	VPG-24
LISTING:	UL 325 Listed 6th Edition / CSA Listed CAN/CSA—C22.2 No. 247
OPERATOR:	Dual belt/high torque reduction system. Counter balanced. Safety locking pins used during preventative maintenance to negate vertical and horizontal movement.
OPERATOR CONSTRUCTION:	Frame: 2" Sq., 11 Ga. (.120) Steel Mounting Pads: 304 SS Skins: 18 Ga. Galvaneal Sheet
OPERATOR SIZE:	Type: VPL-24 Length: 68" Height: 51" Width: 30"
PAINT:	PPG Commercial Coating 2-part High Solids Polyurethane: Standard colors: Black, White, Brown, Green & Gray. Custom colors available.
DUTY CYCLE:	Continuous.
POWER SUPPLY:	120VAC-Single Phase (15 Amp) service (Optional: 240 VAC, 10 Amp) with 24v DC battery back up. (2) Group 24, 12v, Marine Starting, sealed batteries required (NOT INCLUDED!)
POWER MAINTENANCE:	24v built-in battery maintainer keeps batteries charged for built-in battery back-up. "Over-Charge" protection built-in.
CONTROL CIRCUITRY:	Solid state coated control board in electrical enclosure. Sealed proximity switches ensure weather and moisture proof integrity. (Boards tested to -40° F).
CONTROL WIRING:	16 & 18 Ga. single conductor. Copper w/electrolytic copper compression terminals tin-plated for max corrosion prevention.
GEAR MOTOR:	Horse Power: 1/3 Gear Type: Hardened steel Bearing Type: Ball Gear Lube: Dextron II
OPEN / CLOSING CYCLES:	Standard Speed: 10 – 12 seconds
DELAYED CLOSING:	Adjustable from 0 – 60 seconds.
OBSTRUCTION SENSOR:	Adjustable IRD senses obstructions opening or closing.
SECURITY BREACH PROTECTION:	24V built in system brake when 120v or battery power is present.
REVERSING EQUIPMENT:	Optional Reversing/Safety Loop, Leading Reversing Edge, and Infrared Reversing Beams.
OPTIONAL ACCESSORIES:	Access controls, solar power, operator gear motor heater, extreme cold weather package, MUTCD reflective tape, warning lights, audible devices and emergency options (SOS/Opticon/Click-2-Enter).
GATE CONSTRUCTION:	12' - 20': 2" Sq., 11 Ga. (.120) Steel Tubing. Over 20': 2 1/2" Sq., 7 Ga. (.187) Aluminum Tubing
CHAIN LINK CONSTRUCTION:	2 3/8", Sch. 40, 20 & 2" x .065" Galvanized Steel Tubing 9 Ga. Galv. Fabric from 12' up to 22' 2 3/8", Sch. 80, 40 & 2" x 1/8" 6061 Aluminum Tubing 9 Ga. Alum. Fabric over 22' up to 25'
GATE LENGTHS:	10' - 24' (Consult factory for gates over 24')
GATE HEIGHTS:	4' - 8' from pad grade (Barracuda 3'-4'). Consult factory for gates over 8' high. Gates over 8' will require special crating and freight arrangements.
PICKET CONSTRUCTION:	Steel: 3/4" Sq. 18 Ga. Galv. Steel Tubing is standard. Aluminum: 3/4" Aluminum Tubing, 1/8" Wall is standard. Note: Consult factory for special sizes, spacing, and custom material.
GATE HARDWARE:	Gate mounting hardware is 304 stainless steel
WIND BRACING:	Cable: 75 mph design, 1/4" aircraft coated cable 16' - 20' Rigid Masted: Alum. Over 20', compliant with IBC Section 1609.6 Simplified Wind Load Method for 90 mph wind loading and the 150 mph hurricane wind loading.
DOUBLE GATES:	Control Board can be set to accommodate control of a 2nd Operator or Sally Port with another Operator.
SHIPPING WEIGHT:	Typical VPG-24 Operator with 6' high x 20' long picket style gate = 1,600 lbs.
WARRANTY:	Residential: Five (5) years. Industrial/Commercial: Three (3) years from date of shipment on manufactured components and workmanship. Purchased components and accessories are covered under their respective warranties. (see full Warranty for details)

AutoGate, Inc., 7306 Driver Rd., PO BOX 50, Berlin Heights, Ohio 44814

www.AutoGate.com

800-944-4283

Sales@AutoGate.com